



GENERAL NOTES:

1. MATCH EXISTING SURFACE CONDITIONS WITH PAVEMENT REPAIR AS NECESSARY. SEE APPLICABLE DETAILS FOR PAVEMENT CUT REPAIR.
2. MANHOLE SHALL HAVE THE INVERTS PLUGGED WITH A WATER TIGHT MECHANICAL PLUG, PRIOR TO CONCRETE PLUGS.
3. THE CONE SECTION SHALL BE REMOVED AND DISPOSED, THE RING AND COVER SHALL BE REMOVED AND RETURNED TO THE CITY WASTEWATER DEPARTMENT AND THE MANHOLE FILLED IN ACCORDANCE WITH THIS DETAIL.

**SEWER MANHOLE
ABANDONMENT**

NOT TO SCALE

APPROVED

D. J. Powell, P.E. 6-10-16
CITY ENGINEER DATE

CITY OF WICHITA FALLS, TX
ENGINEERING DIVISION

MARCH 2016

SEWER MANHOLE
ABANDONMENT

DETAIL NO. 5170

DISCLAIMER: The use of this standard is governed by the City of Wichita Falls Engineering Department. No warranty of any kind is made by the City of Wichita Falls for any purpose whatsoever. The City of Wichita Falls assumes no responsibility for the conversion of this standard to other formats for incorrect results or damages resulting from its use.