



CROSSWALK STRIPING PLAN

NOTE:

1. STRIPING SHALL BE WHITE, 100 MIL THICK HOT APPLIED THERMOPLASTIC WITH DROP-ON GLASS, TRAFFIC BEADS OR TYPE C PREFABRICATED PAVEMENT MARKINGS. MATERIAL, SURFACE PREPARATION, SEALER, AND INSTALLATION OF CROSSWALK PAVEMENT MARKINGS SHALL BE IN ACCORDANCE WITH ITEMS 666, 668, AND 678 OF TXDOT STANDARD SPECIFICATION FOR CONSTRUCTION AND MAINTENANCE OF HIGHWAYS, STREETS AND BRIDGES.

NOT TO SCALE

APPROVED

D. Phillips, P.E.
CITY ENGINEER

6-13-16
DATE

CITY OF WICHITA FALLS, TX
ENGINEERING DIVISION

MAY 2015

CROSSWALK STRIPING PLAN

DETAIL NO. 2400

DISCLAIMER: The use of this standard is governed by the City of Wichita Falls Engineering Department. No warranty of any kind is made by the City of Wichita Falls for any purpose whatsoever. The City of Wichita Falls assumes no responsibility for the conversion of this standard to other formats for incorrect results or damages resulting from its use.